

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Nitrogen, refrigerated, liquid

Issue Date: Last revised date: 16.01.2013 23.08.2021 Version: 1.4

SDS No.: 000010021831 1/15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier			
Product name:	Nitrogen, refrigerated, liquid		
Trade name:	BIOGON® N suskystintas 3.5 (E941), Suskystintas azotas, Azotas techninis 3.0, Suskystintas azotas 4.8 HiQ, Lazerinis suskystintas azotas 5.0, 5.0 HIGH TECH, ISEQ® Research liquid Nitrogen 5.0		
Additional identification			
Chemical name:	Nitrogen		
Chemical formula:	N2		
INDEX No.	-		
CAS-No.	7727-37-9		
EC No.	231-783-9		
REACH Registration No.	Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH),		
	exempted from registration.		
1.2 Relevant identified uses of the subst	ance or mixture and uses advised against		
Identified uses: Uses advised against	Industrial and professional. Perform risk assessment prior to use. Aerosol propellant. Balance gas for mixtures. Beverage applications. Blanketing gas. Calibration gas. Carrier gas. Cooling applications. Fire suppressant gas. Food freezing. Food packaging gas. Freezing, Cooling and heat transfer. Inerting gas. Inflating tyres. Laboratory use. Laser gas. Pressure head gas, operational assist gas in pressure systems. Process gas. Purge gas. Test gas. Consumer use. Beverage applications. Shielding gas in gas welding. Industrial or technical grade is unsuitable for medical and/or food applications or inhalation.		
1.3 Details of the supplier of the safety d	ata sheet		
Supplier			
Linde Gas UAB Didlaukio g. 69	Telephone: + 370 52787788		

E-mail: sds.ren@linde.com

LT-08300 Vilnius

1.4 Emergency telephone number: Poisons Control and Information Bureau, tel. +370 52 36 20 52



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Issue Date: Last revised date: 16.01.2013 23.08.2021 Nitrogen, refrigerated, liquid Version: 1.4

SDS No.: 000010021831 2/15

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended.

Gases under pressure	Refrigerated	H281: Contains refrigerated gas; may cause cryogenic
	liquefied gas	burns or injury.

2.2 Label Elements

Signal Word:	Warning
Hazard Statement(s):	H281: Contains refrigerated gas; may cause cryogenic burns or injury.
Precautionary Statements General	None.
Prevention:	P282: Wear cold insulating gloves and either face shield or eye protection.
Response:	P336+P315: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.
Storage:	P403: Store in a well-ventilated place.
Disposal	None.
Supplemental information	EIGA-As: Asphyxiant in high concentrations.
2.3 Other hazards	None.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Nitrogen, refrigerated, liquid

Issue Date: Last revised date: 16.01.2013 23.08.2021 Version: 1.4

SDS No.: 000010021831 3/15

SECTION 3: Composition/information on ingredients

31	Substances
J. I	Jubstances

Chemical name	Nitrogen
INDEX No.:	-
CAS-No.:	7727-37-9
EC No.:	231-783-9
REACH Registration No.:	Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH), exempted from registration.
Purity:	100% The purity of the substance in this section is used for classification only, and does not represent the actual purity of the substance as supplied, for which other documentation should be consulted.
Trade name:	BIOGON® N suskystintas 3.5 (E941), Suskystintas azotas, Azotas techninis 3.0, Suskystintas azotas 4.8 HiQ, Lazerinis suskystintas azotas 5.0, 5.0 HIGH TECH, ISEQ® Research liquid Nitrogen 5.0

Chemical name	Chemical formula	Concentration	CAS-No.	REACH Registration No.	M-Factor:	Notes
Nitrogen	N2	100%	7727-37-9	Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH), exempted from registration.	-	

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements. All concentrations are nominal.

This substance has workplace exposure limit(s).

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Nitrogen, refrigerated, liquid

Issue Date:	16.01.2013	Version: 1.4	SDS No.: 000010021831
Last revised date:	23.08.2021		4/15

SECTION 4: First aid measures

General:	In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
4.1 Description of first aid measures	
Inhalation:	In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
Eye contact:	Rinse the eye with water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.
Skin Contact:	Contact with evaporating liquid may cause frostbite or freezing of skin. If clothing is saturated with the liquid and adhering to the skin then the area should be thawed with lukewarm water prior to removing the clothing.
Ingestion:	Ingestion is not considered a potential route of exposure.
4.2 Most important symptoms and effects, both acute and delayed:	Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling.
4.3 Indication of any immediate med	lical attention and special treatment needed
Hazards:	Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling.
Treatment:	Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.
SECTION 5: Firefighting measures	
General Fire Hazards:	Heat may cause the containers to explode.
5.1 Extinguishing media Suitable extinguishing media:	Material will not burn. In case of fire in the surroundings: use appropriate

extinguishing agent.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Nitrogen, refrigerated, liquid

Issue Date: Last revised date:	16.01.2013 Version: 1.4 23.08.2021 23.08.2021		SDS No.: 000010021831 5/15

Unsuitable extinguishing media:	None.
5.2 Special hazards arising from the substance or mixture:	None.
Hazardous Combustion Products:	None.
5.3 Advice for firefighters Special fire fighting procedures:	In case of fire: Stop leak if safe to do so. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Guideline: EN 469 Protective clothing for firefighters. Performance requirements for protective clothing for firefighting. EN 15090 Footwear for firefighters. EN 659 Protective gloves for firefighters. EN 443 Helmets for fire fighting in buildings and other structures. EN 137 Respiratory protective devices - Self-contained opencircuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:	Evacuate area. Provide adequate ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open- circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.
6.2 Environmental Precautions:	Prevent further leakage or spillage if safe to do so.
6.3 Methods and material for containment and cleaning up:	Provide adequate ventilation. Liquid spillages can cause embrittlement of structural materials.
6.4 Reference to other sections:	Refer to sections 8 and 13.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Nitrogen, refrigerated, liquid

Issue Date: Last revised date: 16.01.2013 23.08.2021 Version: 1.4

SDS No.: 000010021831 6/15

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:	Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminates particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.
7.2 Conditions for safe storage, including any incompatibilities:	Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.
7.3 Specific end use(s):	None.

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

None of the components have assigned exposure limits.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Nitrogen, refrigerated, liquid

Issue Date:	
Last revised date:	

16.01.2013 23.08.2021 Version: 1.4

SDS No.: 000010021831 7/15

8.2 Exposure controls	
Appropriate engineering controls:	Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Oxygen detectors should be used when asphyxiating gases may be released. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Systems under pressure should be regularly checked for leakages. Preferably use permanent leak tight connections (eg. welded pipes). Do not eat, drink or smoke when using the product.
Individual protection measures,	such as personal protective equipment
General information:	A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved.
Eye/face protection:	Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.
Skin protection Hand Protection:	Guideline: EN 511 Protective gloves against cold. Additional Information: Wear cold insulating gloves.
Body protection:	Wear apron or protective clothing in case of contact.
Other:	Wear safety shoes while handling containers Guideline: ISO 20345 Personal protective equipment - Safety footwear.
Respiratory Protection:	When allowed by a risk assessment Respiratory Protective Equipment (RPE) may be used The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD. Self-contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres Guideline: EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.
Thermal hazards:	If there is a risk of contact with the liquid, all protective equipment should be suitable for extremely low temperatures.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Nitrogen, refrigerated, liquid

Issue Date:	16.01.2013	Version: 1.4	SDS No.: 000010021831
Last revised date:	23.08.2021		8/15

Hygiene measures:	Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.
Environmental exposure controls:	For waste disposal, see section 13 of the SDS.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	
Physical state:	Gas
Form:	Refrigerated liquefied gas
Color:	Colorless
Odor:	Odorless gas
Odor Threshold:	Odor threshold is subjective and is inadequate to warn of over
	exposure.
pH:	Not applicable.
Melting Point:	-210,01 °C
Boiling Point:	-196 °C
Sublimation Point:	Not applicable.
Critical Temp. (°C):	-147,0 °C
Flash Point:	Not applicable to gases and gas mixtures.
Evaporation Rate:	Not applicable to gases and gas mixtures.
Flammability (solid, gas):	This product is not flammable.
Flammability Limit - Upper (%):	Not applicable.
Flammability Limit - Lower (%):	Not applicable.
Vapor pressure:	No reliable data available.
Vapor density (air=1):	0,97
Relative density:	0,8
Solubility(ies)	
Solubility in Water:	20 mg/l
Partition coefficient (n-octanol/water):	0,67
Autoignition Temperature:	Not applicable.
Decomposition Temperature:	Not known.
Viscosity	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,171 mPa.s (10,9 °C)
DS_LT-000010021831	



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Nitrogen, refrigerated, liquid

Issue Date:	16.01.2013	Version: 1.4	SDS No.: 000010021831
Last revised date:	23.08.2021		9/15

Explosive properties: Oxidizing properties:	Not applicable. Not applicable.
9.2 Other information:	None.
Molecular weight:	28,01 g/mol (N2)

SECTION 10: Stability and reactivity

10.1 Reactivity:	No reactivity hazard other than the effects described in sub-section below.
10.2 Chemical Stability:	Stable under normal conditions.
10.3 Possibility of hazardous reactions:	None.
10.4 Conditions to avoid:	None.
10.5 Incompatible Materials:	Cryogenic liquids can cause embrittlement of some metals and alter the physical properties of other materials. No reaction with any common materials in dry or wet conditions.
10.6 Hazardous Decomposition	Under normal conditions of storage and use, hazardous decomposition products
Products:	should not be produced.
Products: SECTION 11: Toxicological informa	· · · · · · · · · · · · · · · · · · ·
	· · · · · · · · · · · · · · · · · · ·
SECTION 11: Toxicological information	ation None.
SECTION 11: Toxicological information:	ation None.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Nitrogen, refrigerated, liquid

Issue Date:	16.01.2013	Version: 1.4	SDS No.: 000010021831
Last revised date:	23.08.2021		10/15

Acute toxicity - Inhalation Product	Based on available data, the classification criteria are not met.
Skin Corrosion/Irritation Product	Based on available data, the classification criteria are not met.
Serious Eye Damage/Eye Irritat Product	ion Based on available data, the classification criteria are not met.
Respiratory or Skin Sensitization Product	n Based on available data, the classification criteria are not met.
Germ Cell Mutagenicity Product	Based on available data, the classification criteria are not met.
Carcinogenicity Product	Based on available data, the classification criteria are not met.
Reproductive toxicity Product	Based on available data, the classification criteria are not met.
Specific Target Organ Toxicity - Product	Single Exposure Based on available data, the classification criteria are not met.
Specific Target Organ Toxicity - Product	Repeated Exposure Based on available data, the classification criteria are not met.
Aspiration Hazard Product	Not applicable to gases and gas mixtures

SECTION 12: Ecological information

12.1 ToxicityAcute toxicity
ProductNo ecological damage caused by this product.12.2 Persistence and Degradability
ProductNot applicable to gases and gas mixtures..12.3 Bioaccumulative potential
ProductThe subject product is expected to biodegrade and is not expected to persist for
long periods in an aquatic environment.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Nitrogen, refrigerated, liquid

oollution. Not classifi	Version: 1.4 f its high volatility, the product is fed as PBT or vPvB. cal damage caused by this prod	SDS No.: 000010021831 11/15 is unlikely to cause ground or water duct.
oollution. Not classifi	ied as PBT or vPvB.	
		luct.
No ecologio	cal damage caused by this prod	luct.
	charge into any place where its a nere in a well ventilated place.	accumulation could be dangerous. Vent
nttp://ww of containe	/w.eiga.org) for more guidance er via supplier only. Discharge, t	"Disposal of Gases", downloadable at on suitable disposal methods. Dispose treatment, or disposal may be subject to
16 05 05:	Gases in pressure containers of 04.	other than those mentioned in 16 05
(1	of containe	of container via supplier only. Discharge, t national, state, or local laws. 16 05 05: Gases in pressure containers

ADR

IV.		
	14.1 UN Number:	UN 1977
	14.2 UN Proper Shipping Name:	NITROGEN, REFRIGERATED LIQUID
	14.3 Transport Hazard Class(es)	
	Class:	2
	Label(s):	2.2
	Hazard No. (ADR):	22
	Tunnel restriction code:	(C/E)
	14.4 Packing Group:	-
	14.5 Environmental hazards:	Not applicable
	14.6 Special precautions for user:	_



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Nitrogen, refrigerated, liquid

Issue Date:
Last revised date:

16.01.2013 23.08.2021 Version: 1.4

SDS No.: 000010021831 12/15

RID

14.1 UN Number:	UN 1977
14.2 UN Proper Shipping Name 14.3 Transport Hazard Class(es)	NITROGEN, REFRIGERATED LIQUID
Class:	2
Label(s):	2.2
14.4 Packing Group:	-
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	-
IMDG	
14.1 UN Number:	UN 1977
14.2 UN Proper Shipping Name: 14.3 Transport Hazard Class(es)	NITROGEN, REFRIGERATED LIQUID
Class:	2.2
Label(s):	2.2
EmS No.:	F-C, S-V
14.4 Packing Group: 14.5 Environmental hazards:	– Not applicable
14.6 Special precautions for user:	–
ΙΑΤΑ	
14.1 UN Number:	UN 1977
14.2 Proper Shipping Name:	Nitrogen, refrigerated liquid
14.3 Transport Hazard Class(es):	2.2
Class: Label(s):	2.2 2.2, 74C
14.4 Packing Group:	
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	-
Other information	
Passenger and cargo aircraft:	Allowed.
Cargo aircraft only:	Allowed.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Nitrogen, refrigerated, liquid

Issue Date:	16.01.2013	Version: 1.4	SDS No.: 000010021831
Last revised date:	23.08.2021		13/15

Additional identification: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, as amended.: Not applicable

National Regulations

	Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89/686/EEC on personal protective equipment Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives. This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.
15.2 Chemical safety assessment:	Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH), exempted from registration. A CSA does not need to be carried out for this product.

SECTION 16: Other information

Revision Information: Not relevant.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Nitrogen, refrigerated, liquid

Issue Date:	16.01.2013	Version: 1.4	SDS No.: 000010021831
Last revised date:	23.08.2021		14/15

Key literature references and sources for data:	Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to: Agency for Toxic Substances and Diseases Registry (ATSDR) (http://www.atsdr.cdc.gov/). European Chemical Agency: Guidance on the Compilation of Safety Data Sheets. European Chemical Agency: Information on Registered Substances http://apps.echa.europa.eu/registered/registered-sub.aspx#search European Industrial Gases Association (EIGA) Doc. 169 "Classification and Labelling guide", as amended.
	 guide, as amended. International Programme on Chemical Safety (http://www.inchem.org/) ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets. Matheson Gas Data Book, 7th Edition. National Institute for Standards and Technology (NIST) Standard Reference Database Number 69. The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (http://ecb.jrc.ec.europa.eu/esis/).
	The European Chemical Industry Council (CEFIC) ERICards. United States of America's National Library of Medicine's toxicology data network TOXNET (http://toxnet.nlm.nih.gov/index.html) Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH). Substance specific information from suppliers. Details given in this document are believed to be correct at the time of publication.
Wording of the Histophenets in se	ction 2 and 2

Wording of the H-statements in section 2 and 3

H281 Conta	ns refrigerated gas; may cause cryogenic burns or injury.

Training information:Users of breathing apparatus must be trained. The hazard of asphyxiation is often
overlooked and must be stressed during operator training. Ensure operators
understand the hazards.

Classification according to Regulation (EC) No 1272/2008 as amended.

Press. Gas Refrig. Liq. Gas, H281

Other information:Before using this product in any new process or experiment, a thorough material
compatibility and safety study should be carried out. Ensure adequate air ventilation.
Ensure all national/local regulations are observed. Whilst proper care has been
taken in the preparation of this document, no liability for injury or damage resulting
from its use can be accepted.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Nitrogen, refrigerated, liquid

Issue Date: Last revised date: 16.01.2013 23.08.2021 Version: 1.4

SDS No.: 000010021831 15/15

Last revised date: Disclaimer: 23.08.2021

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.